

Dome Camera Comparison Chart

Model	Color- B/W Day/Night	Resolution	Light Level (lux)	Voltage	Power Supply	Housing	Standard Lens	Optional Lenses	Special Features
CVC-927PTZ	Color, Day/Night	480	0.15	24VAC/1AMP/Indoor 24VAC/3AMP/Outdoor	PSW-6	Many Options	18x Optical	No	Speed Dome - Slow Shutter
HT-650PT10X	Color, Day/Night	540	0.5	12VDC	Included	Weather/Tamper ³	3.8-38mm Zoom	No	10X Motorized Optical Zoom & 10X Digital Zoom PTZ
HT-650PTDZ	Color, Day/Night	540	0.5	12VDC	Included	Weather/Tamper ³	4-9mm Auto Iris	No	Motorized Pan & Tilt, 3x Digital Zoom
HT-INTD3	Color, Day/Night	540	.002	12VDC/24VAC Dual Voltage	PSW-4	Weather/Tamper ³	3-9mm	No	Intensifier Series, See color in complete darkness without IR LEDs
HT-INTD4	Color, Day/Night	540	.002	12VDC/24VAC Dual Voltage	PSW-4	Weather/Tamper ³	5-50mm Auto Iris	No	Intensifier Series, See color in complete darkness without IR LEDs
HT-INTD8	Color, Day/Night	560	.002	12VDC/24VAC Dual Voltage	PSW-4	Weatherproof	2.8-12mm	No	Intensifier Series, See color in complete darkness without IR LEDs
HT-INTD9	Color, Day/Night	560	.002	12VDC/24VAC Dual Voltage	PSW-4	Weatherproof	5-50mm	No	Intensifier Series, See color in complete darkness without IR LEDs
HT-INTD10	Color, Day/Night	560	.002	12VDC/24VAC Dual Voltage	PSW-4	Weatherproof	9-22mm	No	Intensifier Series, See color in complete darkness without IR LEDs
CVC-385TP	B/W	420	0.02	12VDC	Included	Weather/Tamperproof	3.6mm	Yes	
CVC-3805TP	B/W	420	0.02	12VDC	Included	Weather/Tamperproof	4-9mm VF AI	No	
CVC-386TP3	B/W	420	0.02	12VDC	Included	Weather/Tamperproof	3.6mm		3-Camera Dome
CVC-6146IHR	Color	550	0.3	12VDC/24VAC Dual Voltage	Included	Normal ³	2.8-11mm	No	Intensifier Series, See color in complete darkness without IR LEDs
CVC-6246IHR	Color, Day/Night	540	0.002	12VDC/24VAC Dual Voltage	Included	Normal ³	2.8-11mm VF AI	No	Intensifier Series, See color in complete darkness without IR LEDs
VL-64TP ^w	Color	420	1	12VDC	Required	Indoor/Tamper	2.9mm	No	
VL-644DC ^w	Color	420	1	12VDC	PSW-5	Normal ³	2.9mm	No	
CVC-645DC ^w	Color	420	.92	12VDC	Included	Normal ³	3.6mm	Yes	Test Connector
HT-647HRT ^w	Color	540	0.5	12VDC	Included	Weather/Tamper ³	3.6mm	Yes	Intensifier, Miniature, Chameleon Cover
CVC-646HR ^w	Color	550	0.5	12VDC	Included	Normal ³	3.6mm	Yes	Ultra High Resolution
CVC-647TP ^w	Color	420	1.0	12VDC	Included	Weather/Tamperproof	3.6mm	Yes	High Resolution, Miniature, Chameleon Cover
CVC-648IRHQ ^w	Color, Day/Night	540	0/0.5*	12VDC	Included	Normal/Wall Mount	3.6mm	Yes	IR LEDs, Special Design Eliminates IR Reflections
CVC-648IRVFHQ	Color, Day/Night	540	0/0.5*	12VDC	Included	Normal/Wall Mount	4-9mm VF AI	No	IR LEDs, Special Design Eliminates IR Reflections
VL-648IR ^w	Color, Day/Night	420	0/1*	12VDC	Included	Normal/Wall Mount	3.6mm	Yes	Wall Mounting bracket included
VL-648IRV ^w	Color, Day/Night	420	0/1*	12VDC	Included	Normal/Wall Mount	4-9mm VF AI	No	Wall Mounting bracket included
HT-INT650 ^{w5}	Color, Day/Night	540		12VDC	Included	Weatherproof	3-12mm	No	Intensifier Series
HT-650IRVFHQ ^{w5}	Color, Day/Night	540	0/5/0*	12VDC	Included	Weather/Tamper	3-12mm VF AI	Yes	22 IR LEDs/Anti-Reflective Technology
WDR-650IRVFHQ ^{w5}	Color, Day/Night	540		12VDC	Included	Weatherproof	3-12mm VF AI	Yes	Wide Dynamic Range/PIXIM
HT-7246iHR	Color, Day/Night	540	0.03	12VDC/24VAC Dual Voltage	PSW4	Weather/Tamper ³ Wall/Ceiling	2.8-11mm VF AI	No	Intensifier Series, Chameleon Cover, Joystick Controlled OSD
HT-7247iHR	Color, Day/Night	540	0.03	12VDC/24VAC Dual Voltage	PSW4	Weather/Tamper ³ Wall/Ceiling	9-22mm VF AI	No	Intensifier Series, Chameleon Cover, Joystick Controlled OSD
CVC-6405	Color	420	.92	12VDC	Included	Normal ³	4-9mm VF AI	Yes	Test Connector
CVC-7WMPDV	Color	480	.5	12VDC/24VAC	Included	Weather/Tamper	4-9mm VF AI	No	Flush or Surface mount
CVC-8WMPDV	Color	580	.5	12VDC/24VAC			2.8-11mm VF AI	No	Wall or Ceiling Mount
CVC-183 ^w	B/W	400	0.2	12VDC	PSW-2	Normal ³	3.6mm	Yes	Economy-Wall/Ceiling Mount
CVC-185	Color, Day/Night	420	0.02	12VDC	Included	Normal	3.6mm	Yes	
CVC-1805DC	B/W	420	0.02	12VDC	Included	Normal	4-9mm VF	No	

* Day/Night dome cameras will display pictures in 0 lux when the IR LEDs are active.

^{w5} Housings are also available in white and silver.

3- Axis mount for wall/ceiling use