Series 25 In-Ceiling Speaker Line

SP525C 5.25” in-ceiling speaker
SP625C 6.5” in-ceiling speaker

Features

- Stylish baffle design
- Pivoting tweeter

sold in pairs

Specifications	SP525C	SP625C
RMS Power	30W	40W
Max. Power	60W	80W
Termintation Type	Press Terminal	Press Terminal
Sensitivity (1W/1M)	87dB	89dB
Maximum SPL (Pmax/1M)	94.3dB	95.5dB
Driver Impedance	8 Ohms	8 Ohms
Magnet	10 oz. ferrite	11.6 oz. ferrite
Frequency Response Range	70Hz ~ 20Hz	50Hz ~ 20Hz
Dispersion @ 1000Hz	85º conical	85º conical
Driver	5.25” Polypropylene woofer	6.5” Polypropylene woofer
	0.75” Silk tweeter	1” Silk tweeter
Speaker Dimensions	8” (Dia.) x 4” (D)	9.25” (Dia.) x 4.25” (D)
Mounting Dimensions	6.6” (Dia.)	7.75” (Dia.)
Minimum Mounting Depth	3.5”	3.75”
Weight	2.4 lbs.	3 lbs.
Material	Baffle: ABS	Baffle: ABS
	Grille: Metal	Grille: Metal
Color	White	White

NDAA COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessories



BRC5
Mounting Bracket
(use with SP525C)



BRC6
Mounting Bracket
(use with SP625C)

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 3/11/22

800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com